

LDMX 1000, 1250, 1500, 1750

SINGLE STAGE, CENTRIFUGAL, MIDSHIP MOUNTED

The LDMX offers an economical solution that offers OEMs the ability to design their own discharge manifold



DIMENSIONS & WEIGHT

- 46" L x 84" W x 32" H, 1,150 lbs. (522 kg)

APPLICATIONS

- Aerial, pumper, pumper tanker, rescue pumper, tanker

STANDARD FEATURES

- 5" NPT or weld discharge flange
- 2 - 5" or 6" NH suction adapters and caps
- 1610 or 1710 full round yokes standard
- Air shift
- 2 1/2" driveline, 12 1/4" driveline drop
- Body width: 70" - 72"
- Heat treated gears

PERFORMANCE

LDMX 1000

1000 gpm (3785 L/M) @ 150 psi (10.3 bar)

700 gpm (2646 L/M) @ 200 psi (13.8 bar)

500 gpm (1893 L/M) @ 250 psi (17.2 bar)

LDMX 1250

1250 gpm (4731 L/M) @ 150 psi (10.3 bar)

875 gpm (3312 L/M) @ 200 psi (13.8 bar)

625 gpm (2365 L/M) @ 250 psi (17.2 bar)

LDMX 1500

1500 gpm (5678 L/M) @ 150 psi (10.3 bar)

1050 gpm (3974 L/M) @ 200 psi (13.8 bar)

750 gpm (2839 L/M) @ 250 psi (17.2 bar)

LDMX 1750

1750 gpm (6624 L/M) @ 150 psi (10.3 bar)

1225 gpm (4637 L/M) @ 200 psi (13.8 bar)

875 gpm (3312 L/M) @ 250 psi (17.2 bar)

